C-DS862i3-ACP

4 Digital Video Port MultiMonitor ACP ThinManager Ready Client



Features

- 4 simultaneous, independent MultiMonitor digital video ports
- Cabling and adapter options available for DisplayPort, HDMI, DVI-D, and VGA (see table for video options below)
- ThinManager Ready, ACP BIOS Enabled
- 1x Gigabit Ethernet port
- 4x USB3.0 ports
- 1x RS-232 serial port
- 1x Line-out audio port
- Super slim and compact design, only 35mm (1.4in) tall
- AC power adapter included

Introduction

Realize the true value of thin client and centralized management technologies with Advantech's ThinManager Compatible industrial thin clients. ACP's ThinManager, the leading thin client solution for the factory floor, and Advantech's industrially hardened thin client hardware provide unique solutions for centralized management of factory floor applications. The C-DS862i3-ACP is the perfect ThinManager MultiMonitor industrial thin client for applications where flexibility and cost savings of 4 monitors per client is desired. The C-DS862i3-ACP supports the newest digital video interfaces such as: DisplayPort, HDMI, and DVI-D.

Specifications

General

- Certification CE, UL, CCC, FCC, BSMI
- Dimensions (WxDxH) 250x190x35mm (9.8x7.5x1.4in) Mounting VESA, Wallmount, Panel Mount
- Power Consumption
- 19VDC, 3.42A (AC power adapter included with lockable DC jack) 2.0kg (4.4lbs)
- Weight

System Hardware

- CPU
- Intel Core i3-3217UE, dual core 2GB DDR3 SDRAM Memory LEDs for Power. LAN Indicators Display AMD Radeon E6460 chipset 2x DisplayPort1.2, 2xDisplayPort1.1 Up to 3840x2160 @ 30Hz each

1x Line-out

(see table below for video options)

Audio

Video Connection Options

AD\ANTEC

Video Port #	DisplayPort	HDMI	DVI-D	VGA
#1	Native	Passive cable	Passive cable	Active Adapter
#2	Native	Passive cable	Passive cable	Active Adapter
#3	Native	Active Adapter	Active Adapter	Active Adapter
#4	Native	Active Adapter	Active Adapter	Active Adapter

I/O Interfaces

- Serial Ports
- LAN
- USB
- 1x RS-232, DB9 port 1x Gigabit, RJ45 port
- 4x USB3.0 ports

Environment

- Humidity
- **Operating Temp**
- **Shock Protection**
- Vibration Protection

10~95% @ 40°C (non-condensing) 0~40°C (32~104°F) with internal fan IEC 60068-2-27 Random 5~500z, 1hr/axis 2 Grms @ 5~500 Hz

Ordering Information

C-DS862i3-ACP

4 Digital Video Port MultiMonitor ACP ThinManager Ready Client (AC power adapter and cord included)

Monitor Cabling Accessories (passive cables)

- XACP-10DP-DPHM-10 DisplayPort to HDMI Cable, 10ft
- XACP-10DP-DPDVI-10 DisplayPort to DVI Cable, 10ft
- XACP-10DP-DPDP-10 DisplayPort to DisplayPort Cable, 10ft

Active Video Adapters (coming soon)

- XXXX
- XXXX •
- DisplayPort to HDMI Adapter DisplayPort to DVI-D Adapter
- XXXX

- DisplayPort to VGA Adapter





20G, half sine, 11 ms IEC60068-2-64