AMT-1021N-D25W1



Features

- 21.5" TFT-LCD panel with LED backlight for 20% power saving and environment protection
- Stylish White with VESA Compatibility
- Dual Signal interface with VGA & DVI
- •0° C ~ 40° C range operating temperature
- •Slim housing design and widescreen format
- Built-in speakers



Introduction

One of the most versatile monitor, AMT-1000, provides great picture quality with a built-in power saving system. It's perfectly designed to fit with Advantech AMiS Computerized Medical Cart. Model Number AMiS-60 and AMiS-50.


(This model doesn't include battery converter and monitor stand)

Specifications

specifications —		
Display	Model	
	Size	21.5" TFT-LCD
	Resolution	1920 x 1080
	View Angel	85°/85° (H) 80°/80° (V)
	Brightness	250 (cd/m²)
	Color Support	16.7M
	Contrast Ratio	1000:1
	Response Time	5 [msec]
	Backlight Life	30000 (hrs)
Environment	Operating Temperature	0~40°C
	Storage Temperature	-20°C~ 60°C
	Humidity	Operating: 20 ~ 80% Non Operating: 10~90%
	Vibration	Vibration Frequency: 5~200Hz,
		Acceleration: 1.038GRMS,
		Test Duration: 30minutes per axis
System	1/0	VGA x1; DVI-D x1;
	OSD	Menu Functions: Brightness, Contrast, Screen Setting,
		Color Temp, VGA/DVI, Recall, Auto Adjust
	Power	Input DC +12Vdc 3.0A
	EMC Compliance	CE, FCC & BSMI

AMT-1021N-D25W1

Drawing



AD\ANTECH Peripheral Allied Procurement Services - Global Sourcing Local Supports -

All product specifications are subject to change without notice.

Last update: 10-18-2013