

C-UNO-1150-ACP

DIN-Rail Single VGA ACP ThinManager Ready Client



Features

- DIN-Rail mount, front port access
- ThinManager Ready, ACP Enabled BIOS
- Single VGA, 1920x1200 maximum resolution
- 2x 10/100BaseT Ethernet ports
- 2x USB2.0 ports
- 1x RS-232 and 2x RS-232/422/485 serial ports
- Audio line In & out
- AC power adapter optional



Introduction

Realize the true value of thin client and centralized management technologies with Advantech's ThinManager Compatible industrial thin clients. ACP's ThinManager, the leading thin client solution for the factory floor, and Advantech's industrially hardened thin client hardware provide a unique solutions for centralized management of factory floor applications. The C-UNO-1150-ACP is the perfect ThinManager Ready industrial thin client for control panel applications where space saving DIN-Rail mounting is needed.

Specifications

General

- **Certification** CE, UL, CCC, FCC
- **Dimensions (WxDxH)** 71x152x139mm
- **Enclosure** Aluminum
- **Mounting** DIN-Rail, Panel Mount
- **Power Consumption** 10 ~ 36 VDC
24VDC @ 1A (15W typical)
AC adapter optional
- **Weight** 1.6kg

System Hardware

- **CPU** AMD Geode LX800 500MHz
- **Memory** 256MB DDR SDRAM
- **Indicators** LEDs for Power, LAN, Serial
- **Display** Single VGA, DB15
1920x1200 max resolution
- **Audio** Line in, Line Out

I/O Interface

- **Serial Ports** 2x RS-232, 2x RS-232/422/485, DB9 ports
- **LAN** 2x 10/100Base-T, RJ45 ports
- **USB** 2x USB2.0 ports
- **Keyboard/Mouse** 1x PS/2 port

Environment

- **Humidity** 20~95% (non-condensing)
- **Operating Temp** -10~60°C (14~140°F)
- **Shock Protection** IEC 60068-2-27
50 G @ wallmount, half sine, 11 ms
- **Vibration Protection** IEC60068-2-64
Random 1 Oct./min, 1hr/axis
2 Grms @ 5~500 Hz

Ordering Information

- **C-UNO-1150-ACP** DIN-Rail Single VGA ACP
ThinManager Ready Client
(excludes AC power adapter)
- **C-UNO-1150-PS-ACP** DIN-Rail Single VGA ACP
ThinManager Ready Client
(includes AC power adapter)